RBM FOAM ADDITIVE





(639526-P)

RBM Building Machinery Trading Sdn Bhd

Head Office: Lot 108, Senawang Industries Estate, 70450 Seremban, Negeri Sembilan, Malaysia.

Tel: (6)06-677 3997 Fax: (6)06-677 4229

H/P: (6)019-621 8880 (Goh) Email: chuawoo@pd.jaring.my



WINNER OF PRODUCT EXCELLENCE INDUSTRY EXCELLENCE AWARD 2008



Good Insulation

Save Cost and Increase Profit



New RBM Technology





FIRE RESISTANCE

 The foam concrete is no reaction occur when expose to fire



WATER RESISTANT

- The foam concrete does not absorb water



GOOD INSULATION

- The foam concrete not a good heat conductor
- Inside the house remain cool



SOUND PROOF

The wall can absorb the echo and reduce the noise



LIGHT WEIGHT

 The concrete has millions of air bubbles trap inside that make it very light.



CAN BE SAWN, NAILED & DRILLED

 The foam concrete is easy to sawn, nailling and drilled without damage the foam concrete's structures

ADDITIVE ITEM:

Description

- 1. Ready-to-used powder admixture with the advanced RBM Technology.
- 2. Specially designed to reduce the weight normal concrete and replaces blocks/bricks.

Features

- Simplify works
- Produce stable foam
- Better workability
- Reduce the concrete weight
- Smoother surface





No Stable









Applications

- 0.1kg (foam additive)+10 to 40kg (Pure water) into foam generator
- Foam Mortar for RBM-1000 (foam concrete machine)
- Able to generate 2000-5000 times of foam from a part of RBM foam additive



Step

1 Packet of RBM Foam Additive 100g



Step 2

Diluted with water about 5 minutes



Fill into RBM Foam Generator



Discharge the foam to mix with mortar