3 IN 1 FOAM CONCRETE MACHINE





ADVANTAGES OF MACHINE



ALL IN ONE

Ready Mix Truck and Mobile Crane for concrete casting does not require anymore.



PACK & GO

Machine able to compact the size and the package is lightweight to carry on truck.



REDUCE LABOURS

Machine require five(5)workers for concrete process.



MATERIALS PREPARATION

Materials such as cement, sand, chipping stone, quarry-dust can be prepare at local resources. RBM additive will improve the quality of concrete



FAST & EASY SETTING UP

Require a small area to setup the machine into a concrete batching, mixing & pumping station at any location.



QUALITY GUARANTEE

All concrete produce by the machine has a consistence & good quality.

MACHINE FEATURES & WORKING PROCESS



CONTROL PANEL SETTING

Control the concrete batching and quality consistency of the mixtures .



CONCRETE PIPING SYSTEM

Easy handling & has strong locking clip (retaining ring) to connect the piping together very fast.



POWERFUL PUMPING SYSTEM

Ability to pump concrete up to 35 storeys heights (125m).



FOAM GENERATOR

Generate foam output to mix with other concrete materials for making Lightweight Concrete.



HIGH PERFORMANCE

It's very durable to work at site condition that require less maintanance. Able to work for 24hours & the output rate is from 0 ~7.5m³ per hour.



AUTO BATCHING System

Built-in with Load Cell System for auto materials batching to produce consistence mixture according to formulation settings.



FOLDABLE CONVEYOR

A 7m length Conveyor can be fold up and flip over to use anytime. Helps deliver materials into mixer.



3 MINS CONCRETE MIX

Mixer built in with special blade stirrer to mix concrete faster & homogeneously.



FILTERING BOARD

Help to filter off particles size more than 10mm in the concrete mix.

STRONG & SOLID BRICK WALL

RBM concrete will shape up according to the formwork without honey-comb because of it high flow-ability.

So choosing a quality formwork system will give a smooth concrete surface as an advantages to apply skim coat as finishing.

Beside that ,it has a high compressive strength that allow air-con, cabinet & photo frame to hang on it.

The process to cast RBM concrete is really fast with the RBM machine.

Local resources materials such as cement, fine adgregates. fly-ash can be take as the concrete ingredients to mix together in the machine.

By adding some additive to the concrete, great advantages will be obtain in the concrete properties to build high quality buildings.

FOAM ADDITIVE Hot Selling!!



Purpose for Foom Concrete (Lightweight) Density : 600kg/m3 to 1800kg/m3 [Concrete can be dril, nat. saw, sanding & modification).

Advantages >

Fre Rasistance Winler Residence nerma insulation Acoustic Insulation Increase Concrete Volume

HARDENER

Hot Selling!!



Purpose for Foam Concrete (Lightweight)

Advantages > Concrete Gook Setting Simplify Works increase Workacitty

Increase Concrete Banding Strength

EASY FLOW

Hot Selling!!



Purpose for Reinforcement Concrete [Recommend for Pump Mix]

Advantages >

Increase Flowability Increase Concrete Banding Strength Prevent Mix Segregation No Vioration Smoother Concrete Sudoce

MORTAR ADDITIVE Contractor





Plastering Advantages >

Prevent Wall Cruck Increase Montal Workapilly high Quarry Plaster Surjace Increase Playfer Banding Strength

ADVANCE FEATURE



CONCRETE INFILL



Plastering Spray Gun



SPRAY PLASTERING

Machine can use for plastering conventional brick wall faster with high quality by installing the spray gun.

A GREAT SAVING ON COST



RM 13.50 /m²



RBM SHEAR WALL: RM 20 /m2



ADVANTAGES



4 HOURS FIRE RATING

It's fire resistance and has no toxic reaction towards fire burning. It also has very low expansion.



LIGHTWEIGHT

It's has a lot of foam bubbles generated and mix in the concrete to make is very light. This help to reduce the design of building dead load.



SELF-LEVELING

High workability, very good flow rate that allow it's easy to do concrete casting/infill & pouring work. Not require any vibration for the concrete.



THERMAL INSULATION

It has a very low density that help to reduce thermal conductivity. This very suitable to use for prevent hot or cold temperature transfer into building.



ACOUSTIC INSULATION

The bubble pores surface repel off the sound from transferring through the concrete.



EASY MODIFICATION

It's can be hack, saw, nail, drill & wall plug without damage or cause any crack on the concrete.



FEATHER LIGHTWEIGHT

Density: 600kg/m3~1000kg/m3 Grade: 2 N/mm2 - 4 N/mm2

LIGHTWEIGHT

Density :1200kg/m2 ~1800kg/m2 Grade: 5 N/mm² ~ 20 N/mm²

HEAVYWEIGHT - REINFORCEMENT

Density: 2100kg/m²

Grade: 25 N/mm2 ~ 35 N/mm2

SUITABLE FOR

WALLS

Party & fire wall External, internal & partition wall

- Lightweight Wall System (Non-Load Bearing)
- · Shear Wall System (Load Bearing Wall)
- Lightweight Block (Cellular)
- Fending

STRUCTURAL

Load bearing wall - grade 25 to 35 Column, beam, slab a staircase

· Building Concrete Structural (Load Bearing)

OTHERS

Cast in situ-formwork infill concrete wall Floor screed


Plastering


- Precast Concrete Products.
- 3D Concrete Volumetric Precast
- . Concrete Decorative products
- Aerated concrete block . Floor Screed Insulation Topping
 - · Swimming Pool, Water Tank
 - · Retaining Wall
 - · Security Bunker, Safety Room, Sound Proof Room



HOW THIS MACHINE WORKS

Program & Setting 2 materials formulation 2 Setup Machine > 1 Loading Materials 3









All Material Can be Use ...

PROJECTS REFERENCES





TERRACE / LINK / HYPERLINK

BUNGALOW & SEMI-D



SHOPLOT







OFFICE

FACTORY



UNIVERSITY & SCHOOL



OPC CEMENT



SAND

WATER









Materials Quantity Quality Control

2 to 3 minutes Continuously 5 Concrete Mixing

Filter object & big particle sizes 6
to provem pump blockage

24 24 1/1

(MY-133290-A)

SPECIFICATION

Machine Engine

Concrete Mixer : 4kW , 380V - 415V ,50Hz High tech Pumping System : 7.5kW ,380V - 415V ,50Hz Conveyor : 0.75kW ,380V - 415V ,50Hz

Speed range : 40rpm - 80rpm

Machine Performance

Concrete Output : 0 - 7.5m³/hr
Pumping Distance : 125m vertical
250m horizontal

Safety Protection

Pump system : Engine Cooling System,

Grease oil

Mixer : Safety Cover, Dust control

sheet

Foam Generator : Pressure gauge

Electrical Valve Safety valve

Foldable Conveyor : Protection Cover Filtering Board : Filter particles above

Ø 8mm

(All above component built in with overload jump switch)

Machine Capacity

Mixer Tank Volume : 650litres Hopper Tank Volume : 650L Foam Generator Volume : 400L Air Compressor Volume : 300L

Foam Generator

Operating Air Pressure : 6bar

Foam Output : 600Litres / min

Conveyor

Belt : High Stress Rubber

Width : 0.35m Length : 7.00m

Dimension

Overall length : 2.50 m Overall width : 1.50 m Overall height : 1.66 m Overall Weight : 980kg



RBM BUILDING MACHINERY SDN. BHD. **Head Office**

Lot 108, Lorong Senawang 4/3, Senawana Industrial Estate. 70450 Seremban, Negeri Sembilan, Malaysia.

06-677 3997

06-677 4229

+6 019-213 5980

Email

rbmtech 0917@hotmail.com

Website

www.rbm.com.my

Channel:

You Tube

www.rbm.com.my

Facebook Page:

rbmbuildingsystem

Visit us now for **GREAT OFFER!**



ECO-FRIENDLY, FAST & QUALITY:

CAST 5 HOUSES

in 10 DAYS ONLY!!

(No more brick works + plastering)



